

Dialogic® Diva® ISDN USB

The Dialogic® Diva® ISDN USB appliance combines USB and digital ISDN technology for high-speed access to the Internet or remote intranets.

The compact design of the ISDN USB allows it to be connected easily to either a desktop or notebook PC, and the USB port provides power.

Along with ISDN remote access, the ISDN USB supports the industry-standard CAPI interface, allowing it to provide access to a wide variety of third-party software for functions such as fax, file transfer, bulletin board access, and voice mail.

Because the ISDN PCI board supports “plug-and-play” and includes intuitive Wizard technology, its installation normally takes only a few minutes.



Features	Benefits
Supports Windows operating system and Microsoft Dial-Up Networking	Provides versatile, flexible Internet and intranet access
Supports Multilink PPP, which combines two 64 kbps ISDN B-channels into a single high-speed 128 kbps pipe, and CAPI for a seamless interface to third-party applications	Supplies full ISDN functionality
Includes RVS-COM Lite for Fax Groups 3 and 4, soft modem, digital answering machine and Euro file transfer functionality; support for a wide variety of Windows applications and ISDN Call Guard for controlling call charges	Provides access to a broad selection of business applications
Installs “plug and play” and includes Wizard technology	Normally installs in a few minutes
Includes Dialogic® Diva® Monitor and 3 LEDs for B-channel status and USB and ISDN connection status; Dialogic® Diva® Assistant and ISDN monitor are available in the system tray	Supplies easy-to-understand monitoring and troubleshooting tools
Microsoft Signature certification and support for multinational ISDN protocols	Can be used internationally

Technical Specifications

Functionality	Fax Group 3: RVS-COM Lite Fax Group 4: CAPI Voice: RVS-COM Lite Compression: RAS client
Operating systems	Windows XP and Windows 2000
Bus type	USB 1.1
Data throughput	128 kbps (2 x 64 kbps)
ISDN port	BRI (S/T)
ISDN connection	Switched and permanent
Protocols	B-Channel: PPP (MLPPP), PAP/CHAP, MS-CHAP, MPPC, HDLC, X.75, X.25/ISO, 8208/X.31, T.70/T.90, V.120, TCP/IP, IPX, NetBEUI D-Channel: EDSS-1 (Euro-ISDN), NI-1 (North America), 5ESS (North America), 1TR6 (Germany), INS Net 64 (Japan), VN4 (France), CTI (Belgium), TPH 1962 (Australia)
Application interface	CAPI 2.0, COM-Port, WAN Miniport
Additional software	RVS-COM Lite Sygate Personal Firewall

Approvals, Compliance, and Warranty

Hazardous substances	RoHS compliance information at http://www.dialogic.com/rohs
Country-specific approvals	See the global product approvals database at http://www.dialogic.com/declarations
Warranty	See warranty information at http://www.dialogic.com/warranties

For more details, go to www.dialogic.com

Dialogic Corporation

9800 Cavendish Blvd., 5th floor
Montreal, Quebec
CANADA H4M 2V9

© 2007 Dialogic Corporation. All rights reserved. Dialogic and Diva are registered trademarks of Dialogic Corporation ("Dialogic"). Dialogic's trademarks may be used publicly only with permission from Dialogic. Such permission may only be granted by Dialogic's legal department at the address provided above. The names of actual companies and products mentioned herein are the trademarks of their respective owners.

Dialogic encourages all users of its products to procure all necessary intellectual property licenses required to implement their concepts or applications, which licenses may vary from country to country. None of the information provided in this product brief other than what is listed under the section entitled Technical Specifications forms part of the specifications of the product and any benefits specified are not guaranteed. No licenses or warranties of any kind are provided under this product brief.

Dialogic may make changes to specifications, product descriptions, and plans at any time, without notice.

10142-01 04/07